

**GET YOUR SAVINGS UP FRONT!**



**The new STREAMLINE STUBBLE GRUBBER cultivator is designed for use in stubble and ploughed land where soil and straw mixing are a priority.**

The Streamline SG is a front linkage mounted cultivator for use directly into stubble ahead of min-till drill and other drill combinations.

Standard tine configuration is 2 rows of heavy spring tines spaced 600mm apart. The 300mm wide wings undercut the stubble for a complete cultivation action and reversible twisted points mix the soil and straw.



This formation combines the aggressive soil and straw movement of the winged and twisted tines with the shattering effect of the heavy spring tines on any clods providing a cultivated and

levelled surface for the following cultivator/drill system.

To help maintain a consistent working depth a pair of adjustable depth wheels are mounted to the front of the Streamline SG



**Standard Specification includes:**

- 2 Rows of Heavy Spring Tines
- Winged and twisted stubble points
- Adjustable Depth Wheels

Folding machines have hydraulic lock out valves fitted to each ram as standard. When the machine is folded for transport or set in the working position the rams are automatically locked into position.

**Working Widths:**

- Rigid - 3m & 4m
- Hydraulic Folding - 4m, 4.8m & 6m.

**Options :** Double headstock for front or rear mounted operation. For further information on our systems please do not hesitate to call our Sales Office.

**STREAMLINE SG Cultivator System**