

Seeders



SEEDERS OVERVIEW

Function	ES4 Standard	ES 8 Standard	ES 8 Turbo	Lehner Vento	HS 8 Turbo	HS 12 Turbo
Control module	Profi	Profi	Profi	Vento	SEED.CON	SEED.CON
			SEED.CON	SEED.CON		
			Profi Speed			
Blower	Electric	Electric	Electric	Electric	Hydraulic	Hydraulic
Power consumption	10 A	10 A	25 A	40 A	5 A / 25 l / minute	5 A / 25 l / minute
Outputs	4	8	8	8	8	12
Hose diameter in mm	30	25	30	30	30	30
Calibration function	Yes	Yes	Yes	Yes	Yes	Yes
Weight in kg	35	50	65	67	110	150
Tank size in l	130	300	300	230	300	500
Dimensions in mm L x W x H	600 x 500 x 1,350	650 x 900 x 1,300	900 x 650 x 1,350	919 x 527 x 1,199	1,250 x 650 x 1,350	1,250 x 700 x 1,660
Maximum working width in m	3	6	6	6	8	9
Standard seed shafts	25	15	15 / 25	Complete set	15 / 25	15 / 25
Suitable for	Grass seeds + small seeds	Grass seeds + small seeds	Grass seeds + various intermediate crops	All seeds	All seeds	All seeds



ACCURATE SOWING.

The right technology for every application – that’s our motto. That’s why we offer different seeder versions with varying functions to meet almost any requirement.

The table on page 22 gives you an overview of what’s on offer. Four different controls are available for the seeders, Profi, Profi Speed, **SEED.CON** and the Lehner Vento control.

The ES 4 Standard, the ES 8 Standard and the ES 8 Turbo with Profi control are intuitive to operate thanks to their simple and practical controls.

This allows the seeder to be easily switched on and off from the cab, the spread rate to be continuously adjusted and a calibration test to be carried out. The **SEED.CON** control module works wirelessly and offers a range of features, such as speed-dependent seed application, as well as hectare and hour counters.

The user-friendly interface on your own smart-phone or tablet makes the control even more practical and simple. All settings can be made either from the cab or directly on the seeder. Further advantages of the **SEED.CON** control system are the quantity control during operation and the additional operation via an ISOBUS terminal.

ADVANTAGES:

- + Sowing close to the ground, less sensitive to wind compared to disc spreaders
- + Exact lateral distribution
- + Spreading in large working widths
- + High tank volume (up to 500 litres)

Convenient to adjust

The **SEED.CON** control’s intuitive user interface makes it particularly convenient to set up your seeder.

